



Compressed air grease gun-DL

M 10 x 1-GBDR-MU

Item number: 18 071
EAN: 4103810180712
Discount group: D

Technical data

Grease gun connection, pressure-side: M 10 x 1
 Filling nipple: M 10 x 1
 Capacity (cm³): 500
 Refilling options: 400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
 Pressure ratio: 50:1
 Grease supply into the grease gun head: spring operated
 Diameter of grease piston (mm): 6
 Grease pump piston actuation: single-stroke grease supply
 Delivery rate/stroke (cm³): 0,8
 Recommended air pressure (bar): 6
 Min. air pressure (bar): 2
 Max. air pressure (bar): 8
 Compressed air connection: hose nozzle, 6 mm, for hose, DN 6 (20 132)
 Pump pressure at 8 bar air pressure (bar): 400
 Burst pressure system (bar): 850
 Burst pressure grease gun head (bar): 1200
 Operation of push rod: with L-design handle
 Cover: loose
 Wall thickness of grease gun tube (mm): 1,0
 Lacquering: silver
 Weight (kg): 1,84

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Angled spout, M 10 x 1, 150 mm (12 635)
- Coupler, 4 jaws, M 10 x 1 (12 631)
- Sales package, with Bar code

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm): 402 x 171 x 84
 Weight including package (kg): 1,99
 Packing unit: 1,0