



# DSE

## Steam Hose

## Application:

Suitable for conveying saturated steam and hot water.

#### Feature:

Electrically conductive: Resistance  $R < 10^6$  Ohm.

#### Notice:

Good resistance to many commercial cleaning agents. If using cleaning agents, please refer to our separate information sheet.

ATTENTION: Use only suitable fittings (clamp fittings according to EN 14423:2005).

ATTENTION: Superheated steam shortens considerably the service life of the hose!

ATTENTION: Please refer to the saturated steam table.

#### Temperature range:

+204°C (saturated steam), +95°C (hot water).

Safety factor: Steam 10: 1, Water 3.15: 1

#### Tube:

EPDM, black, smooth, electrically conductive.

## Reinforcement:

Steel wire braided, zinc-plated.

#### Cover:

EPDM, black, electrically conductive, cloth impression.

## Marking:

Continuous transfer tape – black writing, red background: "SEMPERIT S DSE Sattdampf /Saturated Steam 204°C PN 16bar R< 10 $^6$  Ohm".



Article number	Internal-Ø in		Wall width	External- Ø	Work. pressure (max.) bar		Number of inserts	Bending radius	Weight approx.	Coil length
	mm	inch	in mm	in mm	Satur. steam	Hot water		(min.) in mm	kg/m	(max.) m
48705 1360	13,0	1/2	6,0	25,0	16	50	1	80	0,52	40
48705 1955	19,0	3/4	5,5	30,0	16	50	1	110	0,60	40
48705 1965	19,0	3/4	6,5	32,0	16	50	1	110	0,75	40
48705 2570	25,0	1	7,0	39,0	16	50	1	170	1,00	40
48705 3270	32,0	1 1/4	7,0	46,0	16	50	1	250	1,30	40
48705 3880	38,0	1 1/2	8,0	54,0	16	50	1	350	1,86	40
48705 5090	50,0		9,0	68,0	16	50	2	420	2,40	40

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception. Important notice: Our catalogue and any individual datashest have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620: 2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual and theorem the transmitter of all specifications restrictions in our written product information and applicable laws and standards, the specifications restrictions or to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN ISO 1307:2008.

