



Standard grease gun-HHFP

M 10 x 1-PZ-MU

Item number: 12 630
EAN: 4103810126307
Discount group: A

Technical data

Grease gun connection, pressure-side: M 10 x 1
Capacity (cm³): 500
Refilling options: 400 g grease cartridge, DIN 1284, or bulk grease using a spatula
Diameter of grease piston (mm): 8
Grease pump piston actuation: manually lever operated
Delivery rate/stroke (cm³): 1,2 at a grease density of 0.92 kg/dm³, tested with grease cartridge 400 g (12 511)
Discharge pressure up to (bar): 400
Burst pressure system (bar): 850
Burst pressure grease gun head (bar): 1200
Operation of plunger rod: with L-design handle
Sealing cover: loose
Wall thickness of grease gun tube (mm): 1,0
Lacquering: silver
Dimensions LxWxH (mm): 395 x 120 x 66
Weight (kg): 1,27

Specification

- High pressure hose, M 10 x 1 male, 8 x 300 mm (12 656)
- Hydraulic coupler, M 10 x 1 female (12 631)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- sure grip handling due to deep band knurls
- safe handle on the plunger rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Package: Polybag, printed, with EAN bar code
Dimensions LxWxH (mm): 400 x 360 x 145
Weight including package (kg): 13,1
Packing unit: 10.0